

# GOAL ZERO YETI<sup>®</sup>1400 LITHIUM PORTABLE POWER STATION V2

## On-demand Power from a Gas Generator Alternative

The Goal Zero Yeti 1400 operates with zero fumes and zero noise for an easy-to-use, plug-and-play way to power all your essential electronics and appliances at the push of a button. It's safe enough to store inside your home or apartment for running lights or appliances during an emergency power outage, and still durable enough to take along to your next outdoor project.

## Industry-leading Outputs Including Patented AC and 60W USB-C Power Delivery Ports


With 10 versatile ports to pick from, a Yeti keeps all the necessary gear powered up anywhere. It features higher surge capacities for greater compatibility with more power-hungry devices, and the latest in USB-C Power Delivery capable of charging larger USB devices like laptops.

## WiFi Connected Power Station

Now with WiFi connectivity, simply connect a Yeti through your WiFi router and control it remotely using the new Goal Zero Yeti App. Turn ports on or off, check battery levels, even update the Yeti's firmware with your chosen device. The Goal Zero Yeti App is available now through the Apple App Store or Google Play Store.



### WHAT IT POWERS



### AVAILABLE NOW



| What it charges:                | Approximate charge times:   |
|---------------------------------|---|
| Maximum input                   | 4.5 hrs   |
| Wall charger (5A)               | 25 hrs  |
| Nomad 100                       | 29-57 hrs   |
| Boulder 100 Briefcase           | 29-57 hrs   |
| Boulder 200 Briefcase           | 14-28 hrs   |
| <b>Battery:</b>                 |   |
| Cell chemistry                  | Li-ion NMC  |
| Pack capacity                   | 1425Wh (10.8V, 132Ah)   |
| Single Cell Equivalent Capacity | 396Ah @ 3.6V  |
| Lifecycles                      | 500 Cycles to 80% capacity (Discharge rate: 1C, Full charge/discharge, Temp: 25C) |
| Shelf-life                      | Charge every 3-6 months   |
| Management system               | PWM charge controller, low battery protection                                     |
| <b>Ports:</b>                   |   |
| USB A port (output)             | 5V, up to 2.4A (12W max), regulated   |
| USB C port (output)             | 5V, up to 3.0A (15W max), regulated   |
| USB PD port (output)            | 5V,12V,20V up to 3.0A (60W max)   |
| 6mm port (output, 6mm)          | 12V, up to 10A (120W max)   |
| 12V car port (output)           | 12V, up to 10A (120W max)   |

|  |   |
|--|---|
| 12V Power Pole port (output)<br>(output, pure sine wave) | 12V, up to 20A (240W max)   |
| 120V AC Inverter<br>(output, pure sine wave)             | N/A American Version Only   |
| 230V AC Inverter<br>(output, pure sine wave)             | 230VAC 50Hz, 6.5A (1500W, 3000W surge)  |
| Charging port (input, 8mm)                               | 14-22V, up to 10A (120W max)  |
| Power Pole charging port (input)                         | 14-22V, up to 30A (360W max)  |
| Expansion Module port                                    | Covered port under the lid. To be used with Goal Zero expansion modules only. |
| <b>Wi-Fi:</b>  |   |
| RF Certification   | FCC/CE/IC/TELEC/KCC/SRRC/NCC  |
| Protocols  | 802.11 b/g/n (802.11n up to 150 Mbps)   |
| Frequency Range  | 2.4-2.5 GHz   |
| <b>General:</b>  |   |
| Weight   | 43.7 lbs (19.8 kg)  |
| Dimensions   | 10.1 x 15.3 x 10.4 in (25.7 x 38.9 x 26.4 cm)                                 |
| Operating usage temp.                                    | 32-104 F (0-40 C)   |
| Certs:   |   |
| Warranty   | 12 months   |